Maestro Wireless® product reference guide

What can you do with Maestro Wireless?



Add Convenience

- Control lights from anywhere in a room—or outside the home—with a Pico_® wireless control
- Automate lights with an occupancy sensor to turn on as you enter a space and off again when you leave



Create Ambiance

- Adjust dimmers and lamp dimmers with Pico wireless controls to set the right light level for any activity
- Choose a tabletop lamp dimmer for local or wireless control, or choose the plug-in dimming module, which hides under or behind furniture, and is controlled with a Pico



Enhance Security

- Use a Pico wireless control to turn lights on from your car so you can walk into a well-lit home
- Add a switch where one is needed, rather than crossing a room in the dark—simply mount a Pico wireless control to the wall



Save Energy

- Turn lights off in unoccupied spaces with an occupancy sensor, or remotely as you leave your home with a Pico wireless control
- Turn off appliances in standby mode (such as printers, computers and charging stations) with the plug-in appliance module
- Dim lights to reduce energy usage or use a daylight sensor to automatically adjust light levels based on available daylight





Part numbers & pricing

Maestro Wireless_® load controls

	Lutron P/N	Description	Features	Colors	List Price**
	MRF2-600M-	Maestro Wireless dimmer	Single-pole/multi-location dimmer 120V, 600W incandescent/halogen	All Satin and Gloss colors	\$ 88.00
	MRF2-6MLV-		Single-pole/multi-location dimmer 120 V, 600 W incandescent/halogen, MLV		\$ 100.00
	MRF2-10D-120-		Single-pole/multi-location dimmer 120 V, 1000 W incandescent/halogen, MLV voltage		\$ 130.00
	MRF2-6ND-120-	-	Single-pole/multi-location neutral wire dimmer 120 V, 600 W incandescent/halogen, MLV	_	\$ 130.00
	MA-R-	Maestro companion dimmer	Multi-location companion dimmer 120 V, provides multi-location dimming for up to 9 additional locations		\$ 27.50
	MRF2-8S-DV-	Maestro Wireless switch	Single-pole/multi-location dual volt no-neutral switch, 120 V/277 V, 8 A light, inc./halogen, MLV, ELV, non-dim fluorescent ballasts		\$ 150.00
	MRF2-6ANS-		Single-pole/multi-location switch 120 V, 6 A light or 3 A fan, incandescent, halogen, MLV, ELV, non-dim fluorescent ballasts, and general purpose fans		\$ 88.00
	MRF2-6ANS-277-		Single-pole/multi-location switch 277 V, 6 A light, MLV, ELV, non-dim fluorescent ballasts		\$ 170.00
	MA-AS-	Maestro companion switch	Multi-location companion switch 120 V, provides multi-location switching for up to 9 additional locations		\$ 35.50
	MA-AS-277-		Multi-location companion switch 277 V, provides multi-location switching for up to 9 additional locations		\$ 44.00
	MRF2-3LD-	Maestro Wireless plug-in lamp dimmer	300W, incandescent/halogen for table or floor lamps	WH and BL only	\$ 130.00
	MRF2-3PD-1-	Maestro Wireless plug-in dimming module	Plug-in dimming/switching module; 300 W, inc./ halogen for table or floor lamps, 1 receptacle		\$ 99.00
	MRF2-3PD-3-		Plug-in dimming/switching module; 300 W, inc./ halogen for table or floor lamps, 3 receptacles		\$ 99.00
	MRF2-15APS-1-	Maestro Wireless plug-in appliance module	Plug-in general purpose switch; 15 A, 1 receptacle		\$ 99.00
	MRF2-15APS-3-		Plug-in general purpose switch; 15 A, 3 receptacle		\$ 99.00

Colors and finishes

Satin Colors®

- hot (HT)
- merlot (MR)
- plum (PL)
- turquoise (TQ) sea glass (SG)
- taupe (TP)
- eggshell (ES)
- biscuit (BI)
- snow (SW)
- palladium (PD)
- midnight (MN) sienna (SI)
- terracotta (TC) greenbriar (GB)
- bluestone (BG)
- mocha stone (MS) goldstone (GS)
- desert stone (DS)
- stone (ST)
- limestone (LS)

Gloss colors

- white (WH)
- ivory (IV)
- almond (AL)
- light almond (LA)
- gray (GR)
- brown (BR) black (BL)
- white/gray (WG)
- pico wireless control only

Radio Powr Savr_{TM} wireless sensors & Pico_® wireless controls

		Lutron P/N	Description	Features	Colors	List Price**
	077970 000 11 CC 00 12	LRF2-OCR2B-P-WH*	Radio Powr Savr wireless sensor	360° ceiling-mount occupancy/vacancy sensor, auto-on/auto-off or manual on/auto-off, 3.572" diameter	WH only	\$ 85.00
Latrosc (LRF2-OCRB-P-*		360° ceiling-mount occupancy/vacancy sensor, auto-on/auto-off or manual on/auto-off, 4" diameter	WH, LA and BL only	\$ 130.00
	LRF2-OWLB-P-WH*		180° wall-mount occupancy/vacancy sensor, auto-on/auto-off or manual on/auto-off	WH only	\$ 130.00	
	LRF2-OKLB-P-WH*		90° corner-mount occupancy/vacancy sensor, auto-on/auto-off or manual on/auto-off		\$ 130.00	
	LRF2-OHLB-P-WH*		Hallway occupancy/vacancy sensor, auto-on/auto-off or manual on/auto-off		\$ 130.00	
((LRF2-DCRB-WH		ceiling-mount daylight sensor		\$ 120.00
	Lupe Co.	MRF2-3BRL-L-	Pico wireless control	5-button with on/off, raise/lower and favorite	All gloss colors and white/gray (WG)	\$ 56.00
	7	MRF2-2BRL-L-		4-button with on/off and raise/lower		\$ 56.00
	TOP IN THE PROPERTY OF THE PRO	MRF2-3B-L-		3-button with on/off and favorite		\$ 56.00
		MRF2-2B-L-		2-button with on/off		\$ 56.00
		L-PED1-	Pedestal stand	Single table stand for Pico wireless control	WH and BL only	\$ 60.00
	L-PED2-		Double table stand for Pico wireless control		\$ 80.00	
		CW-1-	Claro wallplate	1-gang opening	All Satin and Gloss colors	\$ 4.90

Packages

Lutron P/N	Description	Features	Colors	List Price**
MRF2-WHK-	Welcome Home package	(1) MRF2-600M-, (1) MRF2-6ANS-, (1) MRF2-3B-L-, and (2) CW-1-	WH and LA only	\$ 242.00
MRF2-600MTHW-	Dimmer and Pico package	(1) MRF2-600M-, (1) MRF2-3BRL-L-, and (1) CW-1-	WH and LA only	\$ 130.00

^{*} Vacancy models available to meet residential California Title 24 section 119(j) requirements—all occupancy/vacancy sensors meet commercial requirements

^{**} List price indicated for gloss colored products

Maestro Wireless® product reference guide

Load controls

Load controls work with Pico wireless controls, occupancy sensors, and/or daylight sensors. Limit 10 total devices.



Dimmer & switch

Width: 2.94" (75mm) Height: 4.69" (119mm)



Lamp dimmer

Width: 2.45" (62mm) Height: 3.23" (82mm) Cord: 6' (1.83m)



Plug-in modules

lamp dimmer or appliance switching versions

Width: 2.25" (57mm) Height: 3.25" (83mm) Socket Cord: 5" (127mm) Plug Cord: 2' (0.6m)

Pico_® wireless controls

Add up to 9 Pico controls to a single load control. Use a single Pico to control up to 9 load controls. Limit 10 total devices.



on/off, raise/lower, & favorite



on/off & raise/lower



on/off & favorite



on/off

Pico wireless control

Width: 1.28" (33mm) Height: 2.60" (66mm) Range: up to 100 ft.

Accessories



Wallmount wallplate sold separately



Car visor clip included





Pedestal—single or double sold separately

Radio Powr Savr wireless sensors

Each sensor works with up to 9 load controls—limit 3 occupancy sensors and 1 daylight sensor per single load control. Limit 10 total devices.



Ceiling-mount occupancy/vacancy* sensor

Diameter: 3.572" (90.73mm)
Depth: 1.30" (33mm)
Range: 60 ft. open air,
30 ft. through walls



Wall/hall/corner occupancy/vacancy* sensor

Width: 1.8" (46mm) Height: 4.35" (110mm) Depth: 1.35" (34mm) Range: 60 ft. open air, 30 ft. through walls



Daylight sensor

Diameter: 1.60" (41mm) Depth: 0.70" (17mm) Range: 60 ft. open air, 30 ft. through walls

*vacancy only sensors available to meet California Title 24 Section 119 (J) requirements



